🏵 VAISALA

Order form

Valid from 6 October 2008

Weather Transmitter		WXT52	0								(
Measurement parameters	Wsd+RH+T+P+R		Α					1	1		
Communication interface	SDI-12 v 1.3, 1200 baud, 7,E,1			A A							ĺ
	RS-232, Standard ASCII auto, 19200 baud,8,N,1			А В							ĺ
	RS-485, Standard ASCII polled, 19200 baud, 8,N,1			A C							ĺ
	RS-422, Standard ASCII auto, 19200 baud, 8,N,1			A D							ĺ
	RS-422 NMEA 0183 v3.0, 4800 baud, 8,N,1			4 E							
	USB/RS-232, 1.4 m USB / M12 cable, ASCII auto, 19200,8,N,1			4 F							
	USB/RS-485, 1.4 m USB / M12 cable, ASCII polled, 19200,8,N,1			4 G							
Enhancements	None				0						
	Heating for wind and rain measurements				1						
Connector	No connector, bushing & ground	ing accessories				A					
	8-pin M12 male connector and bushing & grounding accessories					В					
Cable	No Cable						A				ĺ
						В					
	Shielded 10 meters long 8-pin M12						С				
	Shielded 40 meters long 12-pin cab						D				
	Shielded 10 meters long 8-pin M12						Е				
Installation accessories	None							0			
	Mounting kit	improves classification from	IP65 to IP	66				1			
	Bird spike	P						2			
	Mounting kit and Bird spike improves classification from IP65 to IP66						3				
Supporting software	None								0		
	Service Pack 2: Vaisala Configurati	ion Tool for Windows, USB Service	cable						1		ĺ
Manual language	No manual									Α	ĺ
	English									в	ĺ
	Japanese									J	ĺ
Packing	Standard										0
										т	DTA
Selections in bold are inclu	ided in the prices of the basic version	IS.									QT
Selections in italic are availa	ble at an extra price.								TOT	AL VA	۱LUI
Shielded 40 meters cable does not fit with 8-pin M12 connector		Example of	order cod	e with	ypica	I settin	gs:				
		WXT52	0 A /	A A	0	Α	Α	0	0	Α	0
End customer:								_			
WXT520 Spare parts & Acces	sories										
220614	Service Pack 2: Vaisala Configurati	on Tool for Windows, USB Service	cable								

220614	Service Pack 2: Vaisala Configuration Tool for Windows, USB Service cable
218817SP	WXT520 Radiation shield set
WXTBOTTOMSP	WXT520 Bottom assembly (with BIF card, M12 connector, screws w. O-rings)

WXT510/520 Spare parts & Accessories

220782	USB RS-232/485, 1.4 meters USB / M12 cable
222287	Shielded 2 meters long 8-pin M12 cable
222288	Shielded 10meters long 8-pin M12 cable
217020	Shielded 40 meters long 12-pin cable, open end wires
215952	Shielded 10 meters long 8-pin M12 cable, connectors on both ends
WXTPTUSP	WXT PTU module
222109	Bushing & grounding accessory kit
212792	Mounting kit (improves classification from IP65 to IP66)
WSP150	Surge protector, no connectors
WSP152	Surge protector for host PC (e.g. USB connection) inc. M12 connectors. Suitable with 220782 and 215952.
212793	Bird kit

WXT510 Spare parts & Accessories

215194	Service Pack 1: Vaisala Configuration Tool, Weather Measurements (software and RS-232 WXT510 service cable)
221523	M8 adapter to WXT510 Service connector (use with Service pack 2)

上海博众测量技术有限公司

Bodhi (Shanghai) measurement technology Co.,Ltd. NO.32,ShuPing Road,JiadingDistrict,ZIP201808, Shanghai R.P.China TEL: 0086 21 6630 8161/62/63 FAX: 0086 21 6630 8167