

MMT162 Compact Moisture in Oil and Temperature Transmitter for OEM Applications



The MMT162 enables on-line moisture monitoring in oils even in the most demanding applications.

Features/Benefits

- Continuous measurement of moisture in oil
- Measures in lubrication, hydraulic and transformer oils
- Excellent pressure and temperature tolerance
- Proven Vaisala HUMICAP® Sensor, 15 years in oil applications
- Measures water activity - ppm-calculation available for transformer oil
- Small size, easy to integrate
- Digital output RS-485 with MODBUS
- NIST traceable calibration (certificate included)

The Vaisala HUMICAP® Moisture and Temperature Transmitter for Oil MMT162 is an excellent economical solution for reliable on-line detection of moisture in oil.

Reliable Vaisala HUMICAP® Technology

The MMT162 incorporates the latest generation of the Vaisala HUMICAP® Sensor. The sensor is developed for demanding moisture measurement in liquid hydrocarbons and has been successfully used in oil applications for over a decade. The sensor's excellent chemical tolerance provides accurate and reliable measurement over the measurement range.

Water Activity Measurement

The MMT162 measures moisture in oil in terms of the water activity (aw) and temperature (T). Water activity directly indicates whether there is a risk of free water formation. The measurement is independent of oil type, age and temperature. The ppm calculation for mineral oil based transformer oil is optional in the MMT162.

Several Outputs - One Connector

The MMT162 has two analog outputs that can be scaled and the measurement ranges changed. Additionally, the transmitter has an RS-485 serial output. The signals and the unit power travel in the same cable.

An optional LED-cable enables a visual alarm.

Compact, Rugged and Intelligent

Due to its compact size, the MMT162 is quickly and easily installed in tight spaces. Units are delivered fully assembled, however, you can re-configure them to suit your needs.

MM70

In combination with an MM70 indicator, the MMT162 provides an ideal tool for on site calibration. The MM70 indicator can be used as a display, communication, and data-logging device for the MMT162.

上海博众测量技术有限公司

Bodhi (Shanghai) measurement technology Co.,Ltd.
NO.32,ShuPing Road, Jiading District, ZIP201808,
Shanghai R.P.China
TEL: 0086 21 6630 8161/62/63
FAX: 0086 21 6630 8167

Technical Data

Measured Values

WATER ACTIVITY	
Measurement range	0 ... 1 aw
Accuracy (including non-linearity, hysteresis and repeatability)	
0 ... 0.9	± 0.02
0.9 ... 1.0	± 0.03
Response time	
in oil flow (typical)	<1 min (dry-wet)
MOISTURE	
Calculated moisture content in ppm for mineral transformer oil	
TEMPERATURE	
Accuracy at +20 °C (+68 °F)	± 0.2 °C (0.36 °F)


Operating Environment

Operating temperature	-40 ... +60 °C (-40 ... +140 °F)
Oil temperature	-40 ... +80 °C (-40 ... +176 °F)
Pressure range	
metal version	up to 200 bar
plastic version	up to 40 bar
Oil flow	some flow recommended

Outputs


Analog outputs (two channels)	
current output	0 ... 20 mA, 4 ... 20 mA
voltage output	0 ... 5 V, 0 ... 10 V
Alarm level indication by analog signal	user selectable
Digital outputs	RS-485, non-isolated, Vaisala protocol, MODBUS RTU protocol

Pin	I	II
1	V _{supply}	V _{supply}
2	Ch 1	RS-485 - / B
3	GND	GND
4	Ch 2	RS-485 + / A



Dimensions

Dimensions in mm (inches)



General

Sensor	HUMICAP®
Cable connections (2 ports)	M8, 4 pin
Minimum operating voltage with	
RS-485 output	14 ... 28 VDC
voltage output	16 ... 28 VDC
current output	22 ... 28 VDC
Supply current	
normal measurement	20 mA + load current
External load for	
voltage output	min. 10 kOhm
current output	max. 500 Ohm
Housing material	
metal	AISI 316L
plastic	PPS + 40% GF
Mechanical connections with bonded seal ring (washer)	
metal version	G 1/2" ISO or NPT 1/2"
plastic version	G 1/2" ISO
Housing classification	IP66 (IP65 with plastic housing)
Storage temperature range	-40 ... +80 °C (-40 ... +176 °F)
Weight	
with plastic housing	65 g (2.3 oz)
with metal housing	200 g (7 oz)
Complies with EMC standard EN61326-1, Electrical equipment for measurement control and laboratory use - EMC requirements; Industrial environment	

Options and Accessories

Stainless steel filter (standard)	225356SP
Stainless steel filter for high flow (>1 m/s)	221494SP
Connection cable for MM70 hand-held meter	219980
USB serial interface cable	219690
Sealing ring set (U-seal) ISO G1/2, 3 pcs	221525SP
Sealing ring set (copper) ISO G1/2, 3 pcs	221524SP
ISO 1/2" plug	218773
NPT 1/2" plug	222507
Sampling cell	DMT242SC
Sampling cell w. Swagelok connectors	DMT242SC2
Connection cable	
2 m (6.5 ft), M8 snap-on	211598
0.32 m (1 ft) Shielded, M8 threaded	HMP50Z032
3.0 m (9.8 ft), Shielded, M8 threaded	HMP50Z300SP
5.0 m (16.4 ft), Shielded, M8 threaded	HMP50Z500SP
10 m (32.8 ft), Shielded, M8 threaded	HMP50Z1000SP
3 m, connector 90° angle	221739
5 m, connector 90° angle	221740
M8 threaded, Ch1 signal + Ch2 LED	MP300LEDCBL

VAISALA

上海博众测量技术有限公司

Bodhi (Shanghai) measurement technology Co.,Ltd.
NO.32,ShuPing Road, Jiading District, ZIP201808,
Shanghai R.P.China
TEL: 0086 21 6630 8161/62/63
FAX: 0086 21 6630 8167

Ref. B210755EN-F ©Vaisala 2016